



RULE YOUR RIDE

Year after year, our Talon lineup shows the off-road community just how good a sport side-by-side can be. No other sport UTV offers the level of refinement Honda brings to the game. Our Talon 1000R and 1000R FOX Live Valve are premier two-seaters designed for wide-open spaces and high-performance driving. Both feature our liquid-cooled 999cc Honda Unicam engine and our automatic Dual-Clutch Transmission (DCT) driveline. With the Talon 1000R FOX Live Valve you also get a premium, automatically adjusting active suspension package. And don't forget to check out the rest of our Talon line — if you're looking for a Talon specially tailored for tighter trails, then check out our Talon 1000X, Talon 1000X FOX Live Valve and four-seat Talon models..



2024 Talon 1000R Fox Live Valve

TALONS ARE ONLY FOR DRIVERS 16 YEARS AND OLDER. MULTI-PURPOSE UTILITY VEHICLES (SIDE-BY-SIDES) CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, DRIVE RESPONSIBLY. ALWAYS WEAR A HELMET, EYE PROTECTION, APPROPRIATE CLOTHING AND READ THE OWNER'S MANUAL BEFORE OPERATING THE VEHICLE. ALWAYS WEAR YOUR SEAT BELT, AND KEEP THE SIDE NETS AND DOORS CLOSED. NEVER DRIVE AFTER CONSUMING DRUGS OR ALCOHOL, OR ON PUBLIC ROADS. DRIVER AND PASSENGERS MUST BE TALL ENOUGH FOR SEAT BELT TO FIT PROPERLY AND TO BRACE THEMSELVES WITH BOTH FEET FIRMLY ON THE FLOOR. PASSENGER MUST BE ABLE TO GRASP THE GRAB BAR WITH THE SEAT BELT ON AND BOTH FEET ON THE FLOOR. RESPECT THE ENVIRONMENT WHEN DRIVING. Talon® is a registered trademark of Honda Motor Co., Ltd. ©2024 American Honda Motor Co., Inc.




Talon 1000R




MATTE ABYSS BLACK



**Talon 1000R
Fox Live Valve**


MATTE NAVY BLUE

PEARL RED

FEATURES & BENEFITS

POWERFUL 999cc TWIN-CYLINDER ENGINE

Set longitudinally in the chassis and managed by our sophisticated PGM-FI engine-mapping system, the Talon 1000R's 999cc liquid-cooled inline twin delivers the kind of powerful torque and quick-revving horsepower you want.

FOX LIVE VALVE 2.5 SHOCKS

The Talon 1000R FOX Live Valve features 2.5-inch shocks on all four wheels. The system adjusts damping on each shock independently, automatically, and up to 16 times a second for superior ride quality and less pitch and roll.

AUTOMATIC SIX-SPEED DCT TRANSMISSION

Choose between manual or fully automatic. With DCT you control what engine speed and gear ratio you want, or you can let it do all the thinking for you. You also get genuine engine braking and more efficient power delivery than a belt-driven CVT.

DRIVER/PASSENGER PROTECTION

Large-diameter tubing meets ISO's rollover protection standard. The standard-equipment hard doors and quick-clip side nets help keep debris from entering the cabin. Auto-style three-point seatbelts help optimize passenger security.





2024 Talon 1000RS / Fox Live Valve



Talon 1000R

Talon 1000R Fox Live Valve

ENGINE TYPE	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke	999cc liquid-cooled longitudinally mounted parallel-twin four-stroke
BORE AND STROKE	92.0mm x 75.1mm	92.0mm x 75.1mm
INDUCTION	Fuel Injection (PGM-FI);, 46mm throttle body	Fuel Injection (PGM-FI);, 46mm throttle body
VALVE TRAIN	Unicam® SOHC; four valves per cylinder	Unicam® SOHC; four valves per cylinder
COMPRESSION RATIO	10:1	10:1
TRANSMISSION	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/paddle shifters)	Six-speed automatic Dual-Clutch Transmission (DCT) with high/low subtransmission; two drive modes with 2WD and i-4WD; three shift modes (standard, sport, manual w/ paddle shifters)
DRIVELINE	Direct front and rear driveshafts	Direct front and rear driveshafts
FRONT SUSPENSION	Independent double-wishbone; 17.7 inch travel	Independent double-wishbone with FOX Live Valve shocks; 17.7-inch travel
REAR SUSPENSION	4+ link trailing arm; 20.1-inch travel	4+ link trailing arm with FOX Live Valve shocks; 20.1-inch travel
FRONT BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
REAR BRAKES	Dual 250mm hydraulic discs	Dual 250mm hydraulic discs
FRONT TIRES	28 x 9-15	28 x 9-15
REAR TIRES	28 x 11-15	28 x 11-15
LENGTH	123.7 inches	123.7 inches
WIDTH	68.1 inches	68.1 inches
HEIGHT	75.8 inches	75.8 inches
WHEELBASE	90.0 inches	90.0 inches
BED CAPACITY	299 pounds	299 pounds
SEAT HEIGHT	28.3 inches	28.3 inches
GROUND CLEARANCE	13.2 inches	13.2 inches
CURB WEIGHT	1594 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1596 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel	1587 pounds for 49-state models - Includes all standard equipment, required fluids and full tank of fuel. 1592 pounds for CA models - Includes all standard equipment, required fluids and full tank of fuel
FUEL CAPACITY	7.3 gallons, including 1.1-gallon reserve	7.9 gallons, including 1.1-gallon reserve
TURNING RADIUS	19.4 feet	19.4 feet