



# ADVENTURE BEYOND LIMITS

Adventure calls in two options: the Africa Twin and Africa Twin Adventure Sports ES. Both pack a powerful 1083cc engine and long-distance comfort, plus optional DCT. The standard model journeys off-road with its 21-inch front tire, while the Adventure Sports ES goes the road route with electronic suspension and a 19-inch front wheel. Your journey starts here!

ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, AND NEVER USE THE STREET AS A RACETRACK. RESPECT THE ENVIRONMENT WHEN RIDING. Africa Twin® is a registered trademark of Honda Motor Co., Ltd. Pro-Link® is a registered trademark of Showa Mfg., Inc. Apple CarPlay and iPhone are trademarks of Apple Inc. For using Apple CarPlay, connection to a commercially available Bluetooth headset is necessary. See owner's manual for Bluetooth headset requirements. Unicam® and Pro-Link® are registered trademarks of Honda Motor Co. ©2025 American Honda Motor Co., Inc.



## 2025 Africa Twin/ Adventure Sports ES



**Africa Twin/DCT**



  
MATTE BLACK METALLIC

**Africa Twin  
Adventure Sports ES/DCT**



  
PEARL WHITE

## FEATURES & BENEFITS

### 1083cc TWIN-CYLINDER ENGINE

A narrow 1083cc parallel-twin engine delivers torque smoothly throughout the RPM range, making them great for everything from off-road riding to highway cruising.

### CRUISE CONTROL

All Africa Twin models come factory-equipped with cruise control for touring, and you'll thank us after those high-mileage rides.

### LOW CENTER OF GRAVITY

By placing heavy components like the battery near the bike's center of gravity and using a compact engine, we've created a platform for excellent handling.

### TFT TOUCHSCREEN DISPLAY

A 6.5-inch LCD instrument touch panel features three displays and can show a multitude of information, depending on your needs.







## 2025 Africa Twin/DCT



Africa Twin



Africa Twin Automatic DCT

	Africa Twin	Africa Twin Automatic DCT
<b>ENGINE TYPE</b>	1083cc liquid-cooled Unicam® four-stroke 22.5° parallel-twin	1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin
<b>BORE AND STROKE</b>	92.0mm x 81.5mm	92.0mm x 81.5mm
<b>INDUCTION</b>	PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body	PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body
<b>VALVE TRAIN</b>	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
<b>COMPRESSION RATIO</b>	10.5:1	10.5:1
<b>TRANSMISSION</b>	6-speed manual	6-speed Automatic DCT
<b>FINAL DRIVE</b>	#525 Chain; 16T/42T	#525 Chain; 16T/42T
<b>FRONT SUSPENSION</b>	45mm inverted telescopic fork; 9.0 inches of travel	45mm inverted telescopic fork; 9.0 inches of travel
<b>REAR SUSPENSION</b>	Pro-Link® system w/ single shock; 8.7 inches of travel	Pro-Link system w/ single shock; 8.7 inches of travel
<b>FRONT BRAKES</b>	Dual 310mm discs with four-piston calipers; ABS	Dual 310mm discs with four-piston calipers; ABS
<b>REAR BRAKES</b>	Single 256mm disc with single-piston caliper; ABS	Single 256mm disc with single-piston caliper; ABS
<b>FRONT TIRES</b>	90/90-21	90/90-21
<b>REAR TIRES</b>	150/70R-18	150/70R-18
<b>RAKE</b>	27°	27°
<b>TRAIL</b>	4.5 inches	4.5 inches
<b>WHEELBASE</b>	62.0 inches	62.0 inches
<b>SEAT HEIGHT</b>	Standard position 34.3 inches/Low position 33.5 inches	Standard position 34.3 inches/Low position 33.5 inches
<b>CURB WEIGHT</b>	510 lbs—Includes all standard equipment, required fluids and full tank of fuel	535 lbs—Includes all standard equipment, required fluids and full tank of fuel
<b>FUEL CAPACITY</b>	5.0 gallons including 1.0-gallon reserve	5.0 gallons including 1.0-gallon reserve



# 2025 Africa Twin Adventure Sports ES/DCT



Africa Twin Adventure Sports ES



Africa Twin Adventure Sports ES DCT

<b>ENGINE TYPE</b>	1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin	1083cc liquid-cooled Unicam four-stroke 22.5° parallel-twin
<b>BORE AND STROKE</b>	92.0mm x 81.5mm	92.0mm x 81.5mm
<b>INDUCTION</b>	PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body	PGM-FI electronic fuel injection (Throttle by Wire); 46mm throttle body
<b>VALVE TRAIN</b>	Unicam SOHC; four valves per cylinder	Unicam SOHC; four valves per cylinder
<b>COMPRESSION RATIO</b>	10.5:1	10.5:1
<b>TRANSMISSION</b>	6-speed manual	6-speed Automatic DCT
<b>FINAL DRIVE</b>	#525 Chain; 16T/42T	#525 Chain; 16T/42T
<b>FRONT SUSPENSION</b>	45mm inverted telescopic fork with electronic adjustment; 8.3 inches of travel	45mm inverted telescopic fork with electronic adjustment; 8.3 inches of travel
<b>REAR SUSPENSION</b>	Pro-Link single shock with fork with electronic adjustment ; 7.9 inches of travel	Pro-Link single shock with fork with electronic adjustment ; 7.9 inches of travel
<b>FRONT BRAKES</b>	Dual 310mm discs with four-piston calipers; ABS	Dual 310mm discs with four-piston calipers; ABS
<b>REAR BRAKES</b>	Single 256mm disc with single-piston caliper; ABS	Single 256mm disc with single-piston caliper; ABS
<b>FRONT TIRES</b>	110/80-19	110/80-19
<b>REAR TIRES</b>	150/70R-18	150/70R-18
<b>RAKE</b>	27°	27°
<b>TRAIL</b>	4.2 inches	4.2 inches
<b>WHEELBASE</b>	61.8 inches	61.8 inches
<b>SEAT HEIGHT</b>	Standard position 33.7 inches/Low position 32.9 inches	Standard position 33.7 inches/Low position 32.9 inches
<b>CURB WEIGHT</b>	535 lbs—Includes all standard equipment, required fluids and full tank of fuel	559 lbs—Includes all standard equipment, required fluids and full tank of fuel
<b>CURB WEIGHT</b>	6.6 gallons including 1.0-gallon reserve	6.6 gallons including 1.0-gallon reserve