

MEET OUR NEWEST REBEL

Our Rebel 1100 models are smart, powerful cruisers built for the way we ride today. And this year they're even better: Updates including a bigger instrument screen, Honda RoadSync, more comfortable seats, a more convenient USB port and more. The biggest news? Check out our all-new Rebel 1100 SE, with tasty upgrades like a headlight cowl, bar-end mirrors, short front fender, custom seat, and an awesome Flare Orange Metallic paint scheme.



2025 Rebel 1100 ABS/DCT



Rebel 1100





Rebel 1100 DCT





Rebel 1100 Special Edition





FEATURES & BENEFITS

1083CC TWIN-CYLINDER ENGINE

The powerful parallel-twin engine sets a new standard in its class. Proven in our Africa Twin, it offers ample torque at any RPM, offering power for both easy cruising and free-revving sport riding.

LOW, COMFORTABLE SEAT

An impressively low seat height of 27.5 inches ensures most riders can firmly plant their feet on the ground. It makes for a comfortable ride, confident stops, and easy maneuverability in tight spaces. More foam this year make it even more comfortable!

LOW CENTER OF GRAVITY

We created a platform with unparalleled maneuverability, using a compact engine layout and positioning weighty elements like the crankshaft near the bike's center of gravity.

NEW FIVE-INCH TFT INSTRUMENTS

Of course the big, bright five-inch Thin Film Transistor display gives you all the typical instrument information you want (speedometer, tachometer, time, fuel level, etc.) in a selectable format. But with our new Honda RoadSync app, you can also display music, phone and navigation functions.





2025 Rebel 1100/DCT /Special Edition



| | | TICDOL TIOU DOT | Tiebel 1100 BO1 Opecial Edition |
|-------------------|---|---|---|
| ENGINE TYPE | 1083cc liquid-cooled 22.5° parallel-twin four-stroke | 1083cc liquid-cooled 22.5° parallel-twin four-stroke | 1083cc liquid-cooled 22.5° parallel-twin four-stroke |
| BORE AND STROKE | 92.0mm x 81.5mm | 92.0mm x 81.5mm | 92.0mm x 81.5mm |
| INDUCTION | PGM-FI electronic fuel injection; 46mm throttle body; throttle by wire | PGM-FI electronic fuel injection; 46mm throttle body; throttle by wire | PGM-FI electronic fuel injection; 46mm throttle body; throttle by wire |
| VALVE TRAIN | Unicam SOHC; 4 valves per cylinder | Unicam SOHC; 4 valves per cylinder | Unicam SOHC; 4 valves per cylinder |
| COMPRESSION RATIO | 10.1:1 | 10.1:1 | 10.1:1 |
| TRANSMISSION | Six-speed manual | Six-speed manual | Six-speed manual |
| DRIVELINE | #525 O-ring-sealed chain; 16T/42T | #525 O-ring-sealed chain; 16T/42T | #525 O-ring-sealed chain; 16T/42T |
| FRONT SUSPENSION | 43mm fork; 5.5-inch travel | 43mm fork; 5.5-inch travel | 43mm fork; 5.5-inch travel |
| REAR SUSPENSION | Dual Showa shocks; 3.7-inch travel | Dual Showa shocks; 3.7-inch travel | Dual Showa shocks; 3.7-inch travel |
| FRONT BRAKES | Single 330mm disc with radial-mount four-piston caliper | Single 330mm disc with radial-mount four- piston caliper; ABS | Single 330mm disc with radial-mount four- piston caliper; ABS |
| REAR BRAKES | Single 256mm disc | Single 256mm disc; ABS | Single 256mm disc: ABS |
| FRONT TIRE | 130/70-18 | 130/70-18 | 130/70-18 |
| REAR TIRE | 180/65-16 | 180/65-16 | 180/65-16 |
| RAKE | 28.0° | 28.0° | 28.0° |
| TRAIL | 4.3 inches | 4.3 inches | 4.3 inches |
| WHEELBASE | 59.8 inches | 59.8 inches | 59.8 inches |
| SEAT HEIGHT | 27.5 inches | 27.5 inches | 27.5 inches |
| CURB WEIGHT | 487 pounds (Includes all standard equipment, required fluids and full tank of fuel) | 509 pounds (Includes all standard equipment, required fluids and a full tank of fuel) | 509 pounds (Includes all standard equipment, required fluids and a full tank of fuel) |
| FUEL CAPACITY | 3.6 gallons | 3.6 gallons | 3.6 gallons |
| | | | |