



EXPLORE IN COMFORT

Why choose between comfort and capability when you can have both with our family FourTrax Foreman Rubicon ATVs? You can tackle the toughest trails, work a 12-hour day, or just kick back and explore, and not have to take the next day off to recover. Three distinct models give you the choice to pick your perfect riding partner.



UTILITY ATVS ARE RECOMMENDED FOR RIDERS 16 YEARS AND OLDER. ATVS CAN BE HAZARDOUS TO OPERATE. FOR YOUR SAFETY, BE RESPONSIBLE. READ THE OWNER'S MANUAL. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING. BE CAREFUL ON DIFFICULT TERRAIN. NEVER RIDE AFTER CONSUMING DRUGS OR ALCOHOL, ON PAVED SURFACES, ON PUBLIC ROADS, WITH PASSENGERS, OR AT EXCESSIVE SPEEDS. NO STUNT RIDING. RESPECT THE ENVIRONMENT WHEN RIDING. FourTrax®, Foreman®, Rubicon®, Honda Pro-Connect™, TrueTimber Atera Camo® and TraxLok® are registered trademarks of Honda Motor Co., Ltd. ©2025 American Honda Motor Co., Inc.

**2026 FourTrax
Foreman Rubicon 4x4**



**FourTrax Foreman Rubicon
4x4 EPS
(Electric Power Steering)**



**FourTrax Foreman Rubicon 4x4
Automatic DCT EPS Deluxe
(Dual-Clutch Transmission,
Electric Power Steering)**



FEATURES & BENEFITS

EASY TO USE REVERSE

Available exclusively on our automatic DCT models, this user-friendly single lever is exceptionally handy for seamless forward-to-reverse transitions—perfect for tasks like snow plowing that demand repetitive shifts.

INDEPENDENT REAR SUSPENSION (IRS)

Independent rear suspension enables superior traction via consistent tire contact and a smoother ride over rough terrain.

POWERFUL 518cc ENGINE

Experience unwavering performance with the robust 518cc engine, delivering the power needed on the trails and the job.

TraxLok®

Experience the ultimate in traction optimization with our TraxLok system. Three modes, 2WD, 4WD, and 4WD, with locking front differential and Speed Override, enable increased speed in extreme conditions like mud or snow.





2026 FourTrax Foreman Rubicon 4x4



FourTrax Foreman Rubicon 4x4 EPS

**FourTrax Foreman Rubicon 4x4
Automatic DCT EPS**

**FourTrax Foreman Rubicon 4x4
Automatic DCT EPS Deluxe**

ENGINE TYPE	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke	518cc longitudinally mounted liquid-cooled single-cylinder four-stroke
BORE AND STROKE	96.0mm x 71.5mm	96.0mm x 71.5mm	96.0mm x 71.5mm
INDUCTION	PGM-FI; 36mm throttle body	PGM-FI; 36mm throttle body	PGM-FI; 36mm throttle body
STARTER	Electric with optional auxiliary recoil	Electric with optional auxiliary recoil	Electric with optional auxiliary recoil
VALVE TRAIN	OHV; two valves per cylinder	OHV; two valves per cylinder	OHV; two valves per cylinder
COMPRESSION RATIO	9.5:1	9.5:1	9.5:1
CLUTCH	Automatic	Automatic	Automatic
TRANSMISSION	Five-speed manual with reverse	Five-speed automatic dual-clutch transmission with reverse and Low/Drive subtransmission	Five-speed automatic dual-clutch transmission with reverse and Low/Drive subtransmission
DRIVELINE	Direct front and rear driveshafts with TraxLok® and front differential lock	Direct front and rear driveshafts with TraxLok and front differential lock	Direct front and rear driveshafts with TraxLok and front differential lock
FRONT SUSPENSION	Independent double-wishbone; 7.3 inch travel	Independent double-wishbone; 7.3 inch travel	Independent double-wishbone; 7.3 inch travel
REAR SUSPENSION	Independent double-wishbone; 8.5-inch travel	Independent double-wishbone; 8.5-inch travel	Independent double-wishbone; 8.5-inch travel
FRONT BRAKES	Dual 190mm discs	Dual 190mm discs	Dual 190mm discs
REAR BRAKES	170mm disc	170mm disc	170mm disc
FRONT TIRES	25 x 8-12	25 x 8-12	25 x 8-12
REAR TIRES	25 x 10-12	25 x 10-12	25 x 10-12
LENGTH	86.0 inches	86.0 inches	86.0 inches
WIDTH	47.4 inches	47.4 inches	47.4 inches
HEIGHT	48.7 inches	48.7 inches	48.7 inches
WHEELBASE	50.9 inches	50.9 inches	50.9 inches
SEAT HEIGHT	36.3 inches	36.3 inches	36.3 inches
TOWING CAPACITY	1322 pounds	1322 pounds	1322 pounds
GROUND CLEARANCE	9.8 inches	9.7 inches	9.7 inches
CURB WEIGHT	697 pounds (includes all standard equipment, required fluids and a full tank of fuel)	725 pounds (Includes all standard equipment, required fluids and a full tank of fuel)	719 pounds (Includes all standard equipment, required fluids and a full tank of fuel)
FUEL CAPACITY	3.9 gallons, including 1.3-gallon reserve	3.9 gallons, including 1.3-gallon reserve	3.9 gallons, including 1.3-gallon reserve
TURNING RADIUS	11.5 feet	11.5 feet	11.5 feet
FRONT RACK CAPACITY	99 pounds	99 pounds	99 pounds
REAR RACK CAPACITY	187 pounds	187 pounds	187 pounds

One Year Included Transferable, limited warranty

Optional Extended coverage available with a HondaCare® Protection Plan